



Motor body length can be 115mm, 135mm or 160mm according to different torque.

Main Application :

Mainly used for Automatic Curtains, Stage Lights, Electric Advertisement, Electric Appliances, Pumps, Scientific & Teaching Devices, etc which needs high torque but low speed.

Standard Performances (Test Under Room Temperature) :

Model	Ph.	Rated Volt.	Rated Freq'y	Output Speed	Input Current	Input Power	Max. Torque	Rated Torque	Start Torque	Capacitor	G.W.
		(VAC)	(Hz)	(rpm)	(A)	(W)	(Nm)	(Nm)	(Nm)	(μ F/V)	(Kgs)
NSR110-060-5	1	220	50	60	0.50	90	5.50	5.00	2.00	T9.2/400	6.0
NSR110-060	1	220	50	60	0.55	110	6.00	5.60	2.70	4.0/400	6.0
NSR110-060-2	3	220	50	60	0.65	120	7.50	7.00	3.50		6.0
NSR110-060-3	3	380	50	60	0.38	120	7.50	7.00	3.50		6.0
NSR110-115-5	1	220	50	115	0.60	110	3.80	3.40	1.60	T9.8/400	6.0
NSR110-115	1	220	50	115	0.60	110	4.00	3.60	1.70	4.0/400	6.0
NSR110-115-2	3	220	50	115	0.70	130	6.00	5.40	2.70		6.0
NSR110-115-3	3	380	50	115	0.40	130	6.00	5.40	2.70		6.0

Remarks: The voltage can be changed to any as needed. The torque @ 50Hz is 1.2 times of the torque @ 60Hz.
All above performances are from some typical models only. OEM and ODM are all welcome.

NOSTOP MOTOR GROUP HEAD OFFICE:

BUILDING C#, GANGZHILONG SCIENCE & TECH. INDUS. PARK, HEPING EAST RD., LONGHUA TOWN, SHENZHEN, P.R.CHINA
TEL: (+86.755) 2967 4819, 2967 4809, 2967 4212, 2967 4862, 2983 4766 FAX: (+86.755) 2967 4299
URL: <http://www.nostop.cn>, <http://www.nostopmotor.com> E-mail: stony@nostop.cn Postal Code: 518107